

Key: internal dimensions door opening weight internal capacity

| 20'DC (general purpose 20' x 8' x 8'6") | | |
|---|----------------|------------|
| | length | 5,898 m |
| | width | 2,352 m |
| | height | 2,391 m |
| | width | 2,340 m |
| | height | 2,280 m |
| | max gross | 24.000 kgs |
| | container tare | 2.280 kgs |
| | max payload | 21.720 kgs |
| | volume | 33,2 cbm |

| 40'DC (general purpose 40' x 8' x 8'6") | | |
|---|----------------|------------|
| | length | 12,032 m |
| | width | 2,352 m |
| | height | 2,392 m |
| | width | 2,340 m |
| | height | 2,280 m |
| | max gross | 30.480 kgs |
| | container tare | 3.735 kgs |
| | max payload | 26.745 kgs |
| | volume | 67,7 cbm |

| 40'HC (general purpose 40' x 8' x 9'6") | | |
|---|----------------|------------|
| | length | 12,032 m |
| | width | 2,352 m |
| | height | 2,698 m |
| | width | 2,340 m |
| | height | 2,585 m |
| | max gross | 30.480 kgs |
| | container tare | 3.980 kgs |
| | max payload | 26.500 kgs |
| | volume | 76,3 cbm |

| 45'HC (general purpose 45' x 8' x 9'6") | | |
|---|----------------|------------|
| | length | 13,549 m |
| | width | 2,352 m |
| | height | 2,698 m |
| | width | 2,340 m |
| | height | 2,585 m |
| | max gross | 30.480 kgs |
| | container tare | 4.800 kgs |
| | max payload | 25.680 kgs |
| | volume | 86,0 cbm |

| 20'OT (open top 20' x 8' x 8'6") | | |
|----------------------------------|----------------|------------|
| | length | 5,887 m |
| | width | 2,350 m |
| | height | 2,330 m |
| | width | 2,338 m |
| | height | 2,223 m |
| | max gross | 24.000 kgs |
| | container tare | 2.560 kgs |
| | max payload | 21.440 kgs |
| | volume | 32,2 cbm |

| 40'OT (open top 40' x 8' x 8'6") | | |
|----------------------------------|----------------|------------|
| | length | 12,021 m |
| | width | 2,350 m |
| | height | 2,330 m |
| | width | 2,338 m |
| | height | 2,234 m |
| | max gross | 36.000 kgs |
| | container tare | 4.430 kgs |
| | max payload | 31.570 kgs |
| | volume | 66,7 cbm |

| 20'RF (reefer 20' x 8' x 8'6") | | |
|--------------------------------|----------------|------------|
| | length | 5,455 m |
| | width | 2,294 m |
| | height | 2,288 m |
| | width | 2,268 m |
| | height | 2,215 m |
| | max gross | 24.000 kgs |
| | container tare | 2.950 kgs |
| | max payload | 21.050 kgs |
| | volume | 28,6 cbm |

| 40'RF (reefer 40' x 8' x 8'6") | | |
|--------------------------------|----------------|------------|
| | length | 11,587 m |
| | width | 2,294 m |
| | height | 2,219 m |
| | width | 2,283 m |
| | height | 2,177 m |
| | max gross | 32.000 kgs |
| | container tare | 4.350 kgs |
| | max payload | 27.650 kgs |
| | volume | 58,1 cbm |

| 40'HC RF (reefer 40' x 8' x 9'6") | | |
|-----------------------------------|----------------|------------|
| | length | 11,569 m |
| | width | 2,294 m |
| | height | 2,540 m |
| | width | 2,283 m |
| | height | 2,470 m |
| | max gross | 30.480 kgs |
| | container tare | 4.420 kgs |
| | max payload | 26.060 kgs |
| | volume | 67,4 cbm |

| 20'FR (flat rack 20' x 8' x 8'6") | | |
|-----------------------------------|----------------|------------|
| | length | 5,272 m |
| | width | 2,240 m |
| | height | 2,170 m |
| | max gross | 30.480 kgs |
| | container tare | 2.950 kgs |
| | max payload | 27.530 kgs |
| | volume | 27,9 cbm |

| 40'FR (flat rack 40' x 8' x 8'6") | | |
|-----------------------------------|----------------|------------|
| | length | 12,032 m |
| | width | 2,240 m |
| | height | 2,034 m |
| | max gross | 45.000 kgs |
| | container tare | 5.530 kgs |
| | max payload | 39.470 kgs |
| | volume | 54,8 cbm |

Ovenstående guide til container-specifikationer er udelukkende vejledende